

Frames & Accessories

Frame Specifications & Illustrations

Privacy by *Design*

Frame Details

Information contained below is subject to change. Contact Hy-Lite Customer Service at 888-256-2599 for the most current details.

Extrusion	Frame Dimensions						Frame Colors				Legend
	A Frame Depth	B Glazing Thickness	C Nail Fin Offset	D Flange / J-Channel Width	E Exterior Jamb Thickness	F Interior Jamb Thickness	White	Tan	Drift-wood	Bronze	
V1500	2-3/8"	1-1/2"	1"	N/A	1-9/16"	5/8"	•	•	•	•	<p> A = Overall Frame Depth B = Glazing Thickness C = Nail Fin Offset D = Flange / J-Channel Width E = Exterior Jamb Thickness F = Interior Jamb Thickness </p>
V1580	2-3/8"	1-1/2"	1-3/8"	N/A	1-9/16"	5/8"	•	•	•	•	
V280	2-3/4"	2"	1-3/8"	N/A	1-9/16"	5/8"	•	•	•	•	
VF15FL	3-3/4"	1-1/2"	N/A	1/2"	1-9/16"	5/8"	•	•	•	•	
VT1500	2-3/8"	1-1/2"	1"	1"	1-9/16"	5/8"	•	•	•	•	
BREEZE-LITE	3"	1-1/2"	1"	N/A	3/4"	2-1/2"	•	•	•	•	
VF1500	3-3/4"	1-1/2"	N/A	1-3/4"	1-9/16"	5/8"	•	•	•	•	
VR3000	3-3/4"	1-1/2"	N/A	N/A	1-9/16"	5/8"	•	•	•	•	

New Construction Installation

Window Type	Fixed	Fixed	Fixed	Fixed	Fixed
Drawing (See legend for frame dimensions)					
Extrusion	V1500	V1580	V280	VF15FL	VT1500
Frame Type	Nail Fin	Nail Fin	Nail Fin	Masonry Flange	Nail Fin + J-Channel
Frame Detail	1" Fin Offset	1-3/8" Fin Offset	1-3/8" Fin Offset	1/2" Flush Flange	1" Fin Offset
Material	Vinyl	Vinyl	Vinyl	Vinyl	Vinyl
Block or IG Thickness	1/2" 1" 1-1/2"	1/2" 1" 1-1/2"	1" 1-1/2" 2"	1/2" 1" 1-1/2"	1/2" 1" 1-1/2"

New Construction Installation (cont'd)

Retrofit Installation

Window Type	Awning Casement	Basement Hopper	Fixed	Fixed	Awning Casement Basement Hopper
Drawing (See legend for frame dimensions)					
Extrusion	BREEZE-LITE	BREEZE-LITE	VF1500	VR3000	BREEZE-LITE
Frame Type	Nail Fin	Nail Fin	Flush Flange	Box	Box
Frame Detail	1" 1-3/8" Fin Offset	1" Fin Offset	1-3/4" Flush Flange	Through-Jamb Mount	Through-Jamb Mount
Material	Vinyl	Vinyl	Vinyl	Vinyl	Vinyl
Block or IG Thickness	1" 1-1/2"	1-1/2"	1" 1-1/2"	1" 1-1/2"	1" 1-1/2"